



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- 10 year warranty
- maintenance-free shaft sealing with self-lubricating EPDM lip gasket, replaceable under pressure up to DN 80
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- flange connection
- with sidewise drain valve, rotatable hose connection element G 3/4
- spindle thread not in contact with medium
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- DVGW approval up to DN 80
- WRAS approval
- KIWA approval up to DN 100
- VA approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213 / DIN EN 558-1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	bolt holes	A1	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	Zeta	HS (mm)	cv (m ³ /h)	LS (mm)
1350202500	25	4	G 1/4	70	115	65	25	149	160	13	1	206	24.2	208
1350203200	32	4	G 3/8	70	140	76	32	176	180	15	1.2	244	37.7	236
1350204000	40	4	G 3/8	70	150	84	40	180	200	15	1.3	253	55.4	246
1350205000	50	4	G 3/8	90	165	99	50	221	230	17	0.8	295	112.5	297
1350206500	65	4	G 3/8	90	185	118	65	294	290	17	1.6	338	132.6	337
1350208000	80	8	G 3/8	120	200	132	80	327	310	19	1.4	356	216.3	367
1350210000	100	8	G 3/8	120	220	158	100	302	350	21	2.7	380	240	380
1350212500	125	8	G 3/8	225	250	188	125	488	400	20	3.7	538	320	533
1350215000	150	8	G 3/8	225	285	212	150	295	480	18	3.8	584	460	591

Part no.	kg
1350202500	2.86
1350203200	4.20
1350204000	5.05
1350205000	6.56
1350206500	9.88
1350208000	12.21
1350210000	19.33
1350212500	0.04
1350215000	51.00

Accessories

- gunmetal sampling valve, figure 187 00
- backing ring for stub flange, figure 410 00
- threaded flange, figure 426 00
- stub flange, figure 425 00
- gasket, figure 428 00
- hexagonal bolt and nut, figure 429 M
- extension element for drain valve, figure J6109 473 00

Spare parts

- drain valve made of gunmetal/plastic, figure J7109 173 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- WESER shut off bonnet with extra long shaft, figure E0109 135 02
- handwheel, figure G0100
- threaded plug , figure J8101 173 00
- Installation sleeve for replacement of spindle seal, figure M9100 173 00
- handwheel set, figure 999 00