



### Product Features

- configuration:
  - hose bibb
  - no socket
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- as supply unit to central water supply
- lockable, stainless steel, polished surface
- frame with door with profile cylinder lock as a key lock including bit keys
- retrofittable and interchangeable on an existing locking system
- can be converted on site to CH-KABA lock design
- door with integrated flap version for hose or cable connection for security even during operation
- maintenance-free EPDM spindle seal
- cone with internal CV spring
- can be extended to any length at construction site
- with aerator for automatic drainage
- integrated CV and tube aerator as a security combination HD
- male pipe thread
- actuating grip with blue identification plate
- free from dead spots
- incl. hose coupling for common connection systems
- lock with uniform key number on request, other configurations on request

### Standards and Approvals

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959

### Technical data

- pressure rating PN 16

| Part no.   | DN | A1    | A2    | H1<br>(mm) | H2<br>(mm) | H3<br>(mm) | H4<br>(mm) | H5<br>(mm) | L1<br>(mm) | L2<br>(mm) | T1<br>(mm) | T2<br>(mm) | flow<br>at 0.05 MPa (l/s) | flow<br>at 0.1 MPa (l/s) |
|------------|----|-------|-------|------------|------------|------------|------------|------------|------------|------------|------------|------------|---------------------------|--------------------------|
| 2100801500 | 15 | R 1/2 | G 3/4 | 477.5      | 282.5      | 160        | 28         | 114        | 252.5      | 25         | 121.5      | 56         | 0.4                       | 0.67                     |

| Part no.   | flow<br>at 0.15 MPa (l/s) | kg    |
|------------|---------------------------|-------|
| 2100801500 | 0,8                       | 10,10 |

### Spare parts

- operating cap, figure 590 03 001
- TRESOR lock, figure 210 99 002
- TRESOR lock with uniform key number, figure 210 99 003
- TRESOR mounting plate for sockets, figure E2120 210 03