



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- stainless steel cone
- plastic shaft can be shortened
- can be extended with optional extension kit
- press connection for Geberit MAPRESS pipe
- free from dead spots
- with isolating, balancing and pre-setting function

Standards and Approvals

- DVGW approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- max. installation depth 110 mm
- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	A1 (mm)	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	Zeta	cv (m³/h)
5602201500	15	15	38.5	110	37	55	140	17	20	49	49	98	2.7	5.4
5602201800	15	18	38.5	110	37	55	140	17	20	50.5	50.5	101	2.7	5.4
5602202000	20	22	38.5	110	35	55	145	17	21	50.5	50.5	101	6.9	6
5602202500	25	28	46	115	54	55	180	17	23	68	68	136	4	12.3

Part no.	kg
5602201500	0.71
5602201800	0.70
5602202000	0.74
5602202500	1.34

Accessories

- insulation shell for UP-PLUS and ETA-THERM valves, figure 471 14
- handle for flush-mounted valves, figure 590 00
- operating cover for flush-mounted valves, figure 591 00
- fixing set UP-PLUS, figure 597 00
- UP-PLUS extension set, figure 599 00
- tubular box spanner, size 17/18, 550 mm, figure B5120 500 00

Spare parts

- UP-PLUS inner top part, figure E0109 560 01
- plastic shaft for UP-PLUS flush-mounted valves and UP-PLUS extension set, figure L0100 560 00
- control spindle for flush-mounted valves UP-PLUS, figure P0100 560 00
- UP-PLUS extension spindle, figure P0100 562 00