







## **Product Features**

- configuration:
- frost-proof outdoor valve
- socket 230 V
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- lockable, stainless steel, polished surface
- as supply unit to the central power and water supply
- with SCHUKO surface-mounted socket
- frame with door with profile cylinder lock as a key lock including bit keys
- retroffitable and interchangeable on an existing locking system
- can be converted on site to CH-KABA lock design
- · door with integrated flap version for hose or cable connection for security even during operation
- maintenance-free EPDM spindle seal
- · cone with internal CV spring
- can be extended to any length at construction site
- with aerator for automatic drainage
- integrated CV and tube aerator as a security combination HD
- male pipe thread
- actuating grip with blue identification plate
- free from dead spots
- incl. hose coupling for common connection systems
- lock with uniform key number on request, other configurations on request

## **Standards and Approvals**

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- Valve with BELGAQUA approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- $\bullet$  DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959

## **Technical data**

- pressure rating PN 16
- protection class IP44

Part no.	DN	A1					H3 (mm)	H4 (mm)	H5 (mm)	L1 (mm)				T2 (mm)
2110201500	15	R 1/2	G 3/4	35	283.5	78.5	160	28	114	245	198	51.3	121.5	56

Part no.	flow at 0.05 Mpa (l/s)		flow at 0.15 MPa (l/s)	kg
2110201500	0.4	0.67	0.8	8.88



## **Spare parts**

- TRESOR lock with uniform key number, figure 210 99 003
- TRESOR lock, figure 210 99 002
- operating cap, figure 590 03 001
- hose coupling for Wall-Cabinets TRESOR, figure G3101 210 07
- TRESOR lock cylinder case, figure 210 98 001