



Product Features

- low pressure loss
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- full bore
- female pipe thread
- removable inner top part TOP-ENTRY, with EPDM gasket body and gunmetal ball
- operating handle 90° rotatable
- free from dead spots

Standards and Approvals

- DVGW approval
- WRAS approval
- KIWA UK water regulation 4 approval
- plastic parts with KTW and W 270 approval
- according to DVGW worksheet W 570
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 13828
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 90 °C

| Part no. | DN | A1 | D1 (mm) | H1 (mm) | H2 (mm) | L1 (mm) | T1 (mm) | kg |
|------------|----|--------|------------|------------|------------|------------|------------|------|
| 3850001500 | 15 | Rp 1/2 | 90 | 55.5 | 25 | 84 | 14.5 | 0.51 |
| 3850002000 | 20 | Rp 3/4 | 90 | 55.5 | 25 | 90 | 16.5 | 0.59 |
| 3850002500 | 25 | Rp 1 | 90 | 58.5 | 28 | 99 | 18 | 0.83 |

Accessories

- insulation shell for quarter turn stop valves and CONTROL-PLUS sensors, figure 471 19

Spare parts

- inner top part TOP ENTRY, for quarter turn stop valve and UP quarter turn stop valve for flush-mounted installation, figure E0109 386 00
- handle for quarter turn stop valve, figure 385 00 001