

Product Features

- wetted parts made of stainless steel
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- press connection Geberit MAPRESS
- with sidewise drain valve, rotatable hose connection element G 3/4
- spindle thread not in contact with medium
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- DVGW approval
- SVGW approval
- KIWA approval
- VA approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1 (mm)	A2	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	Zeta	cv (m³/h)	Weight (kg)
0730101500	15	15	G 1/4	60	100	17.5	112	20	22	50	72	2.3	5.9	0.48
0730102000	20	22	G 1/4	60	100	19	125	21	26	57	83	1.6	12.5	0.61
0730102500	25	28	G 1/4	70	128	22.5	146	23	35.5	64.5	100	1.4	21.3	0.91
0730103200	32	35	G 1/4	70	145	24	167	26	34	81	115	1.1	38.7	1.28
0730104000	40	42	G 1/4	70	153	28	189	30	36	92	128	1.8	47.2	1.81
0730105000	50	54	G 1/4	90	195	33	222	35	41	111	152	1.4	84.8	2.89

Accessories

- insulation shell for inclined stop valves, figure 471 10
- SST sampling valve, figure 087 00

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe

Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- stainless steel shut off bonnet, figure E0120 073 02
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100
- Installation sleeve for replacement of spindle seal, figure M9100 173 00

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe