



Product Features

- For digital retrofitting of existing MULTI-THERM installations
- Suitable for retrofitting the KEMPER MULTI-THERM Figures 141, 143, and the KEMPER THERM Figures 140, 142 for the KEMPER MULTI-THERM PRO in the dimension DN15
- For thermoelectronic self-regulating, hydraulic balancing and communication via wireless actuator as wireless control module
- With independent energy generation through energy harvesting
- Communication of the actuator (wireless control module) via radio (LPWAN) with included radio antenna
- Actuator with integrated LED status display
- USB-C port for alternative external power supply
- In combination with the KEMPER PRO WaterManager, Figure 111 01 001: Fully adjustable control range (30–70°C), recording of system temperatures, analysis of operation, and support for thermal disinfection
- Available from 2nd quarter 2026

Part no.	for DN	A1	H1 (mm)	H2 (mm)	SW1 (mm)	SW2 (mm)	Weight (kg)
1440200100	15	G 1/2	32	93	24	27	0.46

Accessories

- PRO WaterManager, with LPWAN, figure 111 01 001

Spare parts

- Radio antenna for MULTI-THERM PRO, figure 144 03 000

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe