



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- spindle with O-ring
- EPDM-seat gasket
- gunmetal cone
- press connection for Geberit MAPRESS pipe
- with plugged drain port
- Pt1000 temperature sensor or thermometer can be added using immersion sleeve
- with green handwheel
- free from dead spots

Standards and Approvals

- DVGW approval
- ÖVGW approval
- VA approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1 (mm)	A2	D1 (mm)	H1 (mm)	L1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	Zeta	cv (m ³ /h)	Weight (kg)
1712201500	15	15	G 1/4	60	97.5	113	20	46	27	73	1.3	5.9	0.42
1712201800	15	18	G 1/4	60	97.5	115	20	28	47	75	1.3	5.9	0.44
1712202000	20	22	G 1/4	60	207	129	20	35	54	89	1.6	12.5	0.61
1712202500	25	28	G 1/4	70	133	149	23	40	63	103	1.4	21.3	1.00
1712203200	32	35	G 1/4	70	162.5	175	26	44.5	78.5	123	1.1	38.7	1.54
1712204000	40	42	G 1/4	70	163.5	204	30	52.5	91.5	144	1.5	47.2	1.99
1712205000	50	54	G 1/4	90	212.5	237.5	35	57	110	167	1.4	84.8	3.16

Accessories

- drain valve made of gunmetal/plastic, figure J7109 173 00
- Pt 1000 temperature sensor, figure T5100 140 00
- insulation shell for inclined stop valves, figure 471 10
- gunmetal sampling valve, figure 187 00
- axial drain valve made of gunmetal, figure J7109 170 00
- dial thermometer, figure T5100 150 00
- extension element for drain valve, figure J6109 473 00
- axial drain valve and immersion sleeve, figure J7109 150 00

Spare parts

- bonnet for ECO stop valve, figure E0101 170 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- threaded plug , figure J8101 173 00