



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- female pipe thread
- spindle thread not in contact with medium
- wear-resistant valve seat made of stainless steel up to DN 50
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- according to DVGW regulations
- according to accepted materials list from German environmental agency
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

| Part no. | DN | A1 | D1 (mm) | H1 (mm) | L1 (mm) | T1 (mm) | Weight (kg) |
|------------|----|----------|---------|---------|---------|---------|-------------|
| 1830201500 | 15 | Rp 1/2 | 60 | 105 | 62 | 13.2 | 0.37 |
| 1830202000 | 20 | Rp 3/4 | 60 | 115 | 74 | 14.5 | 0.52 |
| 1830202500 | 25 | Rp 1 | 70 | 140 | 82 | 16.8 | 0.77 |
| 1830203200 | 32 | Rp 1 1/4 | 70 | 167 | 98 | 19.1 | 1.16 |
| 1830204000 | 40 | Rp 1 1/2 | 90 | 170 | 105 | 19.1 | 1.42 |
| 1830205000 | 50 | Rp 2 | 90 | 202 | 125 | 23.4 | 2.15 |

Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100