


## Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- with suitability verification according to DIN 1988
- maintenance-free EPDM spindle seal
- male threaded inlet, male threaded outlet with hose coupling and cap with chain
- with a black handwheel
- free from dead spots
- Open position indicator
- EPDM-seat gasket

## Standards and Approvals

- according to DVGW regulations
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- according to DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

## Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

| Part no. | DN | A1 | A2 | D1 (mm) | H1 (mm) | L1 (mm) | L2 (mm) | Weight (kg) |
|---|---|---|---|---|---|---|---|---|
| 1850901500 | 15 | G 1/2 | G 3/4 | 60 | 94 | 88.5 | 62 | 0.40 |
| 1850902000 | 20 | G 3/4 | G 1 | 60 | 96 | 104 | 72 | 0.59 |

## Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100

*© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe*