



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- 10 year warranty
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- press connection for Geberit MAPRESS pipe
- with plugged drain port
- Pt1000 temperature sensor or thermometer can be added using immersion sleeve
- spindle thread not in contact with medium
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- DVGW approval
- ÖVGW approval
- SVGW approval
- KIWA approval
- VA approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

| Part no. | DN | A1 (mm) | A2 | D1 (mm) | H1 (mm) | H2 (mm) | L1 (mm) | T1 (mm) | Z1 (mm) | Z2 (mm) | Z3 (mm) | Zeta | cv (m³/h) | kg |
|------------|----|------------|-------|------------|------------|------------|------------|------------|------------|------------|------------|------|--------------|------|
| 1902201500 | 15 | 15 | G 1/4 | 60 | 100 | 21.5 | 94 | 20 | 12 | 42 | 54 | 2.3 | 5.9 | 0.43 |
| 1902201800 | 15 | 18 | G 1/4 | 60 | 100 | 21.5 | 95 | 20 | 12 | 42 | 54 | 2.3 | 5.9 | 0.45 |
| 1902202000 | 20 | 22 | G 1/4 | 60 | 105 | 19.5 | 109 | 21 | 16.5 | 50.5 | 67 | 1.6 | 12.5 | 0.54 |
| 1902202500 | 25 | 28 | G 1/4 | 70 | 132 | 22 | 129.5 | 23 | 20.5 | 63 | 83.5 | 1.4 | 21.3 | 0.82 |
| 1902203200 | 32 | 35 | G 1/4 | 70 | 154 | 27 | 151 | 26 | 29 | 70 | 99 | 1.1 | 38.7 | 1.23 |
| 1902204000 | 40 | 42 | G 1/4 | 70 | 162 | 29.5 | 178 | 30 | 29.5 | 88.5 | 118 | 1.8 | 47.2 | 1.60 |
| 1902205000 | 50 | 54 | G 1/4 | 90 | 193 | 35.5 | 214 | 35 | 44 | 100 | 144 | 1.4 | 84.8 | 2.33 |

Accessories

- Pt 1000 temperature sensor, figure T5100 140 00
- insulation shell for inclined stop valves, figure 471 10
- drain valve made of gunmetal/plastic, figure J7109 173 00
- gunmetal sampling valve, figure 187 00
- dial thermometer, figure T5100 150 00
- axial drain valve and immersion sleeve, figure J7109 150 00
- extension element for drain valve, figure J6109 473 00

Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- WESER shut off bonnet, figure E0109 173 02
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100
- Installation sleeve for replacement of spindle seal, figure M9100 173 00
- threaded plug , figure J8101 173 00