




Product Features

- configuration:
 - frost-proof outdoor valve
 - Switchgear module with 4x Type F safety plug 16 A 2p+E 230 V, 1x CEE socket 16 A 5p 400 V and 1x CEE plug 32 A 5p 400 V
- Made entirely from stainless steel V4A (1.4404)
- Polished surface (320 grit)
- Lockable to prevent unauthorised use
- KEMPER TRESOR complies with protection class IP 45
- Door with integrated flap version for hose or cable connection for security even during use
- Vandal-resistant locking mechanism for the flap
- As a cabinet for water and electricity
- With integrated residual water drainage
- Door frame with profile cylinder lock as a key lock including 3x bit keys
- Functional frame for the application of sealants supplied on site
- retrofittable and interchangeable on an existing locking system
- Lock with uniform key number on request
- A master key system lock is also available on request
- A fully wired and tested switchgear module
- Including frost-proof outdoor tap Frosti figure 579 05
- Socket unit Type F



Standards and Approvals

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- Valve with BELGAQUA approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959 / compliant with DIN EN 61439: RDF 0.79, InA 63A

Technical data

- Switchgear module with 4x Type F safety plug 16 A 2p+E 230 V, 1x CEE socket 16 A 5p 400 V and 1x CEE plug 32 A 5p 400 V

Part no.	DN	A1	A2	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	H6 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)	T3 (mm)	flow at 0.05 MPa (l/s)
2180801500	15	R 1/2	G 3/4	35	518.5	311	130.5	114	37	204	432	198	111	80.5	170.5	56	5	0.4

Part no.	flow at 0.1 MPa (l/s)	flow at 0.15 MPa (l/s)	Weight (kg)
2180801500	0.67	0.8	22.19

Spare parts

- TRESOR lock, figure 210 99 002
- TRESOR lock with uniform key number, figure 210 99 003