



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- gunmetal cone
- plastic shaft can be shortened
- can be extended with optional extension kit
- female pipe thread
- free from dead spots
- Leak detection for inner top part

Standards and Approvals

- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213

Technical data

- max. installation depth 125 mm
- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	A1	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	cv (m³/h)	Weight (kg)
5650101500	15	Rp 1/2	39.5	125	21.45	55	78	17	15	4.25	0.49
5650102000	20	Rp 3/4	39.5	125	21.45	55	82	17	16.3	5.45	0.53
5650102500	25	Rp 1	39.5	135	21.25	65	97	17	19.1	9.10	0.81

Accessories

- final assembly set, figure 595 01
- final assembly set, long version, figure 595 02
- final assembly set, operating cover, figure 595 05
- extension set, figure 599 50 001
- Insulation shell for built-in valves, figure 471 25