



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- gunmetal cone
- plastic shaft can be shortened
- can be extended with optional extension kit
- press connection for Geberit MAPRESS pipe
- free from dead spots
- Leak detection for inner top part

Standards and Approvals

- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213

Technical data

- max. installation depth 125 mm
- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	A1 (mm)	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	cv (m ³ /h)	Weight (kg)
5652201500	15	15	39.5	125	21.45	55	138.4	17	20	49.2	49.2	98.4	4.25	0.61
5652201800	15	18	18.2	125	21.45	55	141	17	20	50.5	50.5	101	4.25	0.62
5652202000	20	22	39.5	125	21.45	55	141	17	20	50.5	50.5	101	5.45	0.67
5652202500	25	28	49.5	135	21.25	65	172	17	23	63	63	126	9.10	1.05

Accessories

- final assembly set, figure 595 01
- final assembly set, long version, figure 595 02
- final assembly set, operating cover, figure 595 05
- extension set, figure 599 50 001
- Insulation shell for built-in valves, figure 471 25