



Product Features

- construction set version, suitable for the brick shell installation and for the subsequent installation in completed outer wall
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- universal length for all common installation depths
- inner top part for quick opening operation (two turns)
- cone with internal CV spring
- EPDM-seat gasket
- can be extended with optional extension kit
- integrated CV and tube aerator as a security combination HD
- inlet male pipe thread
- free from dead spots
- incl. hose coupling for common connection systems
- high discharge capacity of up to 45 l/min (1 bar)
- with theft-proof aerator for automatic drainage
- incl. fastened anti-twist protection
- incl. two-part drop ear elbow for wall-flush closing
- discharge body with mounting surfaces
- with theft-proof socket key operated

Standards and Approvals

- DVGW approval according to DIN EN 17821
- ÖVGW approval
- SVGW approval
- KIWA approval
- BELGAQUA approval
- VA approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- EN 1717

Technical data

- min. installation depth 150 mm
- max. installation depth 415 mm
- pressure rating PN 16
- max. operating temperature 65 °C

Part no.	DN	A1	A2	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	flow at 0.05 MPa (l/s)	flow at 0.1 MPa (l/s)	flow at 0.15 MPa (l/s)
5780301500	15	R 1/2	G 3/4	100	35	81	71.5	556	415	122	66.5	434	0.46	0.67	0.82
5780302000	20	R 3/4	G 1	100	35	81	86.5	558	415	122	69	436	0.52	0.75	0.92

Part no.	Weight (kg)
5780301500	1.85
5780302000	1.93

Accessories

- FROSTI® lockable handle, figure 578 00 003
- FROSTI® lockable handle, for uniform key, figure 578 02 003
- FROSTI® extension, figure 578 00 002
- FROSTI® fastening set, figure 578 00 005
- FROSTI® sealing sleeve set, figure 578 00 006
- FROSTI® special extension, figure 578 03 005

Spare parts

- FROSTI® socket key operated head part with socket key, figure 578 00 001
- FROSTI® handle, figure 578 01 001
- FROSTI® inner top part, figure 578 35 001
- FROSTI® spindle XL with cone, figure 578 33 001
- FROSTI® spindle XL with cone without CV, figure 578 34 001
- FROSTI® breather, figure 578 23 001
- FROSTI® plug-in tube diffuser, figure 578 24 020
- FROSTI® spindle XL, figure 578 32 001
- FROSTI® hose coupling, figure 578 25 015
- FROSTI® hose coupling seal disc, figure 578 27 001
- FROSTI® hose coupling, figure 578 25 020
- FROSTI® socket key, figure 578 00 004
- FROSTI® DN20 hose coupling adapter, figure 578 26 001
- FROSTI® two-piece collar, figure 578 28 001
- FROSTI® discharge body, complete, figure 578 02
- FROSTI® assembly set, socket key operated, figure 578 10