




Product Features

- easily replaceable double mesh made of stainless steel
- female pipe thread
- for any installation position



Technical data

- pressure rating PN 16
- max. operating temperature 200 °C
- mesh width outer supporting sieve 0.6 mm
- mesh width inner screen 0.3 mm

| Part no. | DN | A1 | H1 (mm) | L1 (mm) | SW1 (mm) | T1 (mm) | Zeta | cv (m ³ /h) | Weight (kg) |
|------------|----|----------|------------|------------|-------------|------------|------|---------------------------|----------------|
| 6020001500 | 15 | Rp 1/2 | 40 | 65 | 22 | 12 | 3.8 | 4.6 | 0.23 |
| 6020002000 | 20 | Rp 3/4 | 50 | 75 | 24 | 14 | 4.5 | 7.5 | 0.40 |
| 6020002500 | 25 | Rp 1 | 55 | 90 | 32 | 15 | 4.8 | 11.3 | 0.55 |
| 6020003200 | 32 | Rp 1 1/4 | 70 | 112 | 36 | 17 | 3.5 | 21.7 | 0.89 |
| 6020004000 | 40 | Rp 1 1/2 | 80 | 120 | 46 | 17 | 5 | 28.4 | 1.25 |
| 6020005000 | 50 | Rp 2 | 95 | 150 | 55 | 20 | 4.4 | 47.1 | 1.80 |

Spare parts

- double screen insert for strainer 602, figure E3120 602 00