

Product Features

- suitable for Stop Valves with flange connection e.g. figure 135
- incl. EPDM-bonnet gasket
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket

Standards and Approvals

- according to UBA BWGL Metals
- for valves acc. DIN 3502

Part no.	for DN	A1	A1	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	H2 (mm)	Weight (kg)
E010913502015KP	15	G 1/2	N/A	60	26.4	16.4	127	19.5	0.21
E010913502020KP	20	G 3/4	N/A	60	32.4	22	150	26	0.23
E010913502025KP	25	G 1	N/A	70	39.9	28	168	26.8	0.38
E010913502032KP	32	G 1 1/4	N/A	70	49.9	36	197	27.8	0.54
E010113502040KP	40	G 1 1/2	N/A	70	57.9	41.5	208	40.8	0.60
E010113502050KP	50	G 2	N/A	90	69.9	53	233	42.3	0.92
E010113502065KP	65	G 2 1/2	N/A	120	87.9	68	323	34.1	1.77
E010113502080KP	80	G 3	N/A	120	101.9	81	360	35.1	2.13
E010113500100KP	100	N/A	M110 x 2	120	120.9	100	292	68	3.27
E010113500125KP	125	N/A	M142 x 2	225	155	125	450	56.6	10.11
E010113500150KP	150	N/A	N/A	225	175	155	486	115	15.80

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe