



### Product Features

- wetted parts made of stainless steel
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- press connection Geberit MAPRESS
- without drain port (drain valve cannot be added)
- spindle thread not in contact with medium
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- Open position indicator

### Standards and Approvals

- DVGW approval
- SVGW approval
- KIWA approval
- VA approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÚA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

### Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1 (mm)	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	Zeta	cv (m <sup>3</sup> /h)	kg
0730001500	15	15	60	100	17.5	112	20	22	50	72	2.3	5.9	0.41
0730002000	20	22	60	100	19	125	21	26	57	83	1.6	12.5	0.52
0730002500	25	28	70	128	22.5	146	23	35.5	64.5	100	1.4	21.3	0.86
0730003200	32	35	70	145	24	167	26	34	81	115	1.1	38.7	1.19
0730004000	40	42	70	153	28	189	30	36	92	128	1.8	47.2	1.75
0730005000	50	54	90	195	33	222	35	41	111	152	1.4	84.8	2.81

### Accessories

- insulation shell for inclined stop valves, figure 471 10

### Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- stainless steel shut off bonnet, figure E0120 073 02
- handwheel, figure G0100
- Installation sleeve for replacement of spindle seal, figure M9100 173 00