


## Product Features

- thermostatic balancing valve for hydraulic balancing of very short circulation circuits from kv-min ≥ 0.05
- for hydraulic balancing of hot water return systems (PWH-C), supports thermal disinfection
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- PTFE seat gasket
- maintenance-free EPDM spindle seal
- thermostatic balancing unit
- male union thread
- handle grip with purple identification plate
- free from dead spots
- with isolating, balancing and pre-setting function

## Standards and Approvals

- DVGW approval
- ÖVGW approval
- SVGW approval
- according to UBA KTW BWGL
- for systems according to DVGW worksheet W 551 / W 553 / DIN 1988-300
- according to UBA BWGL Metals
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

## Technical data

- control range 62 °C - 64 °C
- pressure rating PN 16
- max. operating temperature 90 °C

| Part no. | DN | A1 | D1 (mm) | H1 (mm) | H2 (mm) | L1 (mm) | SW1 (mm) | cv ($m^3/h$) | Weight (kg) |
|---|---|---|---|---|---|---|---|---|---|
| 1340G01500 | 15 | G 3/4 | 42 | 47 | 35 | 86.5 | 19 | 0.4 | 0.51 |

## Accessories

- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- insulation shell for UP-PLUS and ETA-THERM valves, figure 471 14
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- hexagon socket key, size 19, figure B5120 599 00
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70

## Spare parts

- Balancing bonnet 62-64°C for ETA-THERM thermostatic balancing valve, figure E0109 540 01

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe