

Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle gasket with self-lubricating EPDM lip gasket
- EPDM-seat gasket
- flange connection
- with sidewise drain valve, rotatable hose connection element G 3/4
- with test port
- check valve with SST spring
- with a black handwheel
- free from dead spots
- for any installation position
- with shut-off function
- Open position indicator

Standards and Approvals

- according to DVGW regulations
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- acc. to DIN EN 13959 provisions / DIN EN 558-1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	bolt holes	A1	A2	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	Zeta	Δ $p_{opening}$ (hpa)	cv (m^3/h)	Weight (kg)
1370205000	50	4	G 1/4	G 3/8	90	165	102	50	220	230	14	2.3	70	64.7	6.53
1370206500	65	4	G 1/4	G 3/8	120	185	122	65	293	290	15	2.1	120	116	11.17
1370208000	80	8	G 1/4	G 3/8	120	200	138	80	326	310	16	3.8	140	130	12.86
1370210000	100	8	G 1/4	G 3/8	120	220	158	100	302	350	18	3.8	140	186	19.10

Accessories

- backing ring for stub flange, figure 410 00
- gunmetal sampling valve, figure 187 00
- stub flange, figure 425 00
- threaded flange, figure 426 00
- gasket, figure 428 00
- hexagonal bolt and nut, figure 429 M

Spare parts

- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- bonnet with check function for combined stop and check valve, figure E0101 137 00
- bonnet with check function for combined stop and check valve, figure E0101 160 01
- threaded plug , figure J8101 173 00

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe