



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- female pipe thread
- spindle thread not in contact with medium
- wear-resistant valve seat made of stainless steel up to DN 50
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- according to DVGW regulations
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1	D1 (mm)	H1 (mm)	L1 (mm)	T1 (mm)	Weight (kg)
1830201500	15	Rp 1/2	60	105	62	13.2	0.37
1830202000	20	Rp 3/4	60	115	74	14.5	0.52
1830202500	25	Rp 1	70	140	82	16.8	0.77
1830203200	32	Rp 1 1/4	70	167	98	19.1	1.16
1830204000	40	Rp 1 1/2	90	170	105	19.1	1.42
1830205000	50	Rp 2	90	202	125	23.4	2.15

Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100