



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- with suitability verification according to DIN 1988
- maintenance-free EPDM spindle seal
- male threaded inlet, male threaded outlet with hose coupling and cap with chain
- with a black handwheel
- free from dead spots
- Open position indicator
- EPDM-seat gasket

Standards and Approvals

- according to DVGW regulations
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- according to DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1	A2	D1 (mm)	H1 (mm)	L1 (mm)	L2 (mm)	Weight (kg)
1850901500	15	G 1/2	G 3/4	60	94	88.5	62	0.40
1850902000	20	G 3/4	G 1	60	96	104	72	0.59

Spare parts

- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe