



Product Features

- to sample drinking water and determine microbiological parameters according to the German TrinkwV drinking-water regulation
- for simple retrofitting at the output of the angle valve
- suitable for angle valves with 10 mm outlet compression connection
- sampling pipe can be disinfected by flame
- valve completely chrome-plated
- PTFE seat gasket
- inlet 10 x 1.25 pipe, outlet G3/8 male thread with compression nut for 10 mm pipe
- valve is operated with 5 mm allen key (not in package)
- made of brass, nickel plated
- free from dead spots

Standards and Approvals

- DVGW approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- UBA BWGL Metalle & DVGW W 551-8

Technical data

- pressure rating PN 10
- max. operating temperature 90 °C

Part no.	DN	A1	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	L1 (mm)	L2 (mm)	SW1 (mm)	SW2 (mm)	SW3	Weight (kg)
1880001000	10	G 3/8	10	8	65	26	153.5	110.5	52.5	41	19	15	5	0.29

Spare parts

- drain elbow for angled sampling valve, figure 188 99 002

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe