

Product Features

- configuration:
  - frost-proof outdoor valve
  - Electrical mounting plate with 1x Type G safety plug 13 A 2p+E 230 V socket and 1x CEE socket 16 A 5p 400 V
- Made entirely from stainless steel V4A (1.4404)
- Polished surface (320 grit)
- Lockable to prevent unauthorised use
- KEMPER TRESOR complies with protection class IP 45
- Door with integrated flap version for hose or cable connection for security even during use
- Vandal-resistant locking mechanism for the flap
- As a cabinet for water and electricity
- With integrated residual water drainage
- Door frame with profile cylinder lock as a key lock including 3x bit keys
- Functional frame for the application of sealants supplied on site
- retroffitable and interchangeable on an existing locking system
- Lock with uniform key number on request
- A master key system lock is also available on request
- Including frost-proof outdoor tap Frosti figure 579 05
- Type G socket combination unit

Standards and Approvals

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- Valve with BELGAQUA approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959

Technical data

- Electrical mounting plate with 1x Type G safety plug 13 A 2p+E 230 V socket and 1x CEE socket 16 A 5p 400 V

Part no.	DN	A1	A2	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)	T3 (mm)	flow at 0.05 MPa (l/s)
21603015UK	15	R 1/2	G 3/4	35	366.5	148	130.5	114	36.5	318	198	64.5	23.5	140.5	56	5	0.4

Part no.	flow at 0.1 MPa (l/s)	flow at 0.15 MPa (l/s)	Weight (kg)
21603015UK	0.67	0.8	11.66

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe