




## Product Features

- configuration:
  - frost-proof outdoor valve
  - Electrical mounting plate with 2x Type F safety plug 16 A 2p+E 230 V sockets and 1x CEE socket 32 A 5p 400 V
- Made entirely from stainless steel V4A (1.4404)
- Polished surface (320 grit)
- Lockable to prevent unauthorised use
- KEMPER TRESOR complies with protection class IP 45
- Door with integrated flap version for hose or cable connection for security even during use
- Vandal-resistant locking mechanism for the flap
- As a cabinet for water and electricity
- With integrated residual water drainage
- Door frame with profile cylinder lock as a key lock including 3x bit keys
- Functional frame for the application of sealants supplied on site
- retrofittable and interchangeable on an existing locking system
- Lock with uniform key number on request
- A master key system lock is also available on request
- Including frost-proof outdoor tap Frosti figure 579 05
- Type G socket combination unit



## Standards and Approvals

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- Valve with BELGAQUA approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 14367 / DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959

## Technical data

- Electrical mounting plate with 2x Type F safety plug 16 A 2p+E 230 V sockets and 1x CEE socket 32 A 5p 400 V

| Part no.   | DN | A1    | A2    | D1 (mm) | H1 (mm) | H2 (mm) | H3 (mm) | H4 (mm) | H5 (mm) | H6 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | T1 (mm) | T2 (mm) | T3 (mm) | flow at 0.05 MPa (l/s) |
|------------|----|-------|-------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------------------------|
| 21805015UK | 15 | R 1/2 | G 3/4 | 35      | 518.5   | 311     | 130.5   | 114     | 37      | 204     | 432     | 198     | 111     | 80.5    | 170.5   | 56      | 5       | 0.4                    |

| Part no.   | flow at 0.1 MPa (l/s) | flow at 0.15 MPa (l/s) | Weight (kg) |
|------------|-----------------------|------------------------|-------------|
| 21805015UK | 0.67                  | 0.8                    | 18.43       |