



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water

Standards and Approvals

- according to accepted materials list from German environmental agency
- similar to DIN 2642
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 200 °C

| Part no. | DN | hole pattern (PN) | bolt holes | D1 (mm) | D2 (mm) | D3 (mm) | D4 (mm) | S1 (mm) | kg |
|------------|-----|-------------------|------------|------------|------------|------------|------------|------------|------|
| 4100004000 | 40 | 10/16 | 4 | 150 | 110 | 50 | 18 | 16 | 2.07 |
| 4100005000 | 50 | 10/16 | 4 | 165 | 125 | 62 | 18 | 16 | 2.44 |
| 4100006500 | 65 | 10/16 | 4 | 185 | 145 | 82 | 18 | 16 | 2.92 |
| 4100008000 | 80 | 10/16 | 8 | 200 | 160 | 96 | 18 | 18 | 3.53 |
| 4100010000 | 100 | 10/16 | 8 | 220 | 180 | 119 | 18 | 18 | 3.92 |
| 4100012500 | 125 | 10/16 | 8 | 250 | 210 | 145 | 18 | 18 | 4.79 |
| 4100015000 | 150 | 10/16 | 8 | 285 | 240 | 170 | 22 | 18 | 6.03 |