



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- stainless steel cone
- plastic shaft can be shortened
- can be extended with optional extension kit
- female pipe thread
- free from dead spots
- with isolating, balancing and pre-setting function

Standards and Approvals

- DVGW approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- max. installation depth 110 mm
- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	A1	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	Zeta	cv (m³/h)	kg
5600101500	15	Rp 1/2	38.5	110	37	55	80	17	15	2.7	5.4	0.56
5600102000	20	Rp 3/4	38.5	110	35	55	90	17	16.3	6.9	6	0.62
5600102500	25	Rp 1	46	115	54	55	120	17	19.1	4	12.3	1.12
5600103200	32	Rp 1 1/4	46	115	53	55	124	17	21.4	5.7	16.9	1.33

Accessories

- insulation shell for UP-PLUS and ETA-THERM valves, figure 471 14
- tubular box spanner, size 17/18, 550 mm, figure B5120 500 00
- handle for flush-mounted valves, figure 590 00
- operating cover for flush-mounted valves, figure 591 00
- UP-PLUS extension set, figure 599 00

Spare parts

- UP-PLUS inner top part, figure E0109 560 01
- plastic shaft for UP-PLUS flush-mounted valves and UP-PLUS extension set, figure L0100 560 00
- control spindle for flush-mounted valves UP-PLUS, figure P0100 560 00
- UP-PLUS extension spindle, figure P0100 562 00