

Product Features

- pre-assembled
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- suitable for fast subsequent installation on already finished outer wall
- inner top part for quick opening operation (two turns)
- high discharge capacity of 40 l / min (1 bar)
- EPDM-seat gasket
- can be extended to any length at construction site
- inlet male pipe thread
- free from dead spots
- incl. hose coupling for common connection systems
- flexible installation length with sliding wall disc in outdoor area
- matt chrome-plated handle with over-twist protection
- with theft-proof socket key operated
- with theft-proof aerator for automatic drainage
- discharge body with mounting surfaces

Standards and Approvals

- WRAS approval
- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1
- EN 1717

Technical data

- min. installation depth 150 mm
- pressure rating PN 16
- max. operating temperature 65 °C

Part no.	DN	A1	A2	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	T1 (mm)	flow at 0.05 MPa (l/s)	flow at 0.1 MPa (l/s)
5791101500	15	R 1/2	G 3/4	35	15	71.5	114	100	363	242	122	61.5	495	253.5	56	0.46	0.67

Part no.	flow at 0.15 MPa (l/s)	Weight (kg)
5791101500	0.82	1.44

Accessories

- FROSTI® lockable handle, figure 578 00 003
- FROSTI collar XL, figure 577 12 015
- FROSTI® lockable handle, for uniform key, figure 578 02 003

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe

Spare parts

- FROSTI® socket key operated head part with socket key, figure 578 00 001
- FROSTI® spindle XL with cone without CV, figure 578 34 001
- FROSTI® socket key, figure 578 00 004

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe