

Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- easily replaceable double mesh made of stainless steel
- flange connection
- for any installation position

Standards and Approvals

- according to UBA BWGL Metals
- DIN EN 558-1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 200 °C
- mesh width outer supporting sieve 0.6 mm
- mesh width inner screen 0.3 mm

Part no.	DN	bolt holes	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	SW1 (mm)	Zeta	cv (m^3/h)	Weight (kg)
6050005000	50	4	165	99	50	91	230	17	50	4.4	47.1	5.88
6050006500	65	4	185	118	65	101	290	17	60	4.2	81.6	9.75
6050008000	80	8	200	132	80	116	310	19	60	3.9	128	12.63
6050010000	100	8	220	158	100	151	350	21	70			16.85

Accessories

- backing ring for stub flange, figure 410 00
- stub flange, figure 425 00
- threaded flange, figure 426 00
- gasket, figure 428 00

Spare parts

- double screen insert for strainer figure 605, figure E3120 605 00

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe