



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- housing with G 2 coaxial thread for meter cartridges
- consisting of flush-mounted valve and water meter housing with plaster work protectors
- installation depth variable within the installation dimensions of the water meter
- for installation of a cold or hot-water metering cartridge
- as a one-piece cast water meter section
- maintenance-free EPDM spindle seal
- female pipe thread
- free from dead spots
- cast-on mounting feet with sound decoupling

Standards and Approvals

- flush-mounted UP valve(s) DVGW approval
- according to accepted materials list from German environmental agency
- flush-mounted valve with soundproofing certificate according to DIN EN ISO 3822 Class 1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- inside micrometer 120 mm
- pressure rating PN 10
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

| Part no. | DN | A1 | H1 (mm) | H2 (mm) | H3 (mm) | H4 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | L5 (mm) | T1 (mm) | cv (m³/h) | kg |
|------------|----|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|------|
| 8554702000 | 20 | Rp 3/4 | 105 | 75 | 31 | 24 | 234 | 120 | 44 | 140 | 64 | 16.3 | 4.1 | 1.59 |

Accessories

- RG120 grip top die-cast zinc set-up dimensions to 32 mm, figure 596 11
- RG120 grip top die-cast zinc set-up dimensions 30 mm to 110 mm, figure 596 12
- RG120 grip top plastic set-up dimensions up to 32 mm, figure 596 16
- RG120 grip-top plastic, set-up dimensions 30 mm to 110 mm, figure 596 17
- RG120 change stopper including extension for set-up dimensions to 110 mm, figure 596 15
- cap for stop valve water meter combinations and mounting blocks, figure 855 00 002

Spare parts

- RG120 inner top part, figure E0109 854 00 020