



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- for Techem water meter cartridges
- consisting of two flush-mounted valves and water meter housings with plaster work protectors
- installation depth variable within the installation dimensions of the water meter
- for installation of a cold and hot water
- of two one-piece cast water meter sections
- maintenance-free EPDM spindle seal
- female pipe thread
- free from dead spots
-

Standards and Approvals

- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- to meet the requirements of GEG 2023
- building material class B1 according to DIN 4102
- CE marking

Technical data

- inside micrometer 120 mm
- pressure rating PN 16
- max. operating temperature 60 °C

Part no.	DN	A1	H1 (mm)	H2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)	cv (m ³ /h)	Weight (kg)
8640502000	20	Rp 3/4	136	73	234	215	120	44	300	150	2.75	2.98

Accessories

- final assembly set, figure 595 01
- final assembly set, long version, figure 595 02
- final assembly set, operating cover, figure 595 05
- fixing set, figure 863 15 001
- extension set, figure 599 50 001
- blank cover plate, figure 865 00 001