



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- consisting of flush-mounted valve and water meter housing with plaster work protectors
- installation depth variable within the installation dimensions of the water meter
- for installation of a cold and hot water
- as a one-piece cast water meter section
- maintenance-free EPDM spindle seal
- female pipe thread
- free from dead spots
- cast-on mounting feet with sound decoupling
-

Technical data

- inside micrometer 65 mm
- max. installation depth 32 mm
- pressure rating PN 16
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

| Part no. | DN | A1 | H1 (mm) | H2 (mm) | H3 (mm) | H4 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | L5 (mm) | T1 (mm) | cv (m ³ /h) | Weight (kg) |
|------------|----|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------------------------|-------------|
| 8650702000 | 20 | Rp 3/4 | 136 | 73.7 | 30.5 | 24 | 170 | 65 | 44 | 87 | 64 | 16.3 | 3 | 1.20 |

Accessories

- final assembly set Mono, figure 595 03
- final assembly set Mono, operating cover, figure 595 06