

Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- housing with G 2 coaxial thread for meter cartridges
- consisting of flush-mounted valve and water meter housing with plaster work protectors
- installation depth variable within the installation dimensions of the water meter
- for installation of a cold and hot water
- as a one-piece cast water meter section
- maintenance-free EPDM spindle seal
- female pipe thread
- free from dead spots
- cast-on mounting feet with sound decoupling
- Leak detection for inner top part and water meter mounting
- With universal multi-water meter bodies G 2 coaxial
- Center distance only 120 mm

Standards and Approvals

- according to UBA KTW BWGL
- according to UBA BWGL Metals
- soundproofing certification according to DIN EN ISO 3822 Class 1

Technical data

- inside micrometer 120 mm
- pressure rating PN 16
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

Part no.	DN	A1	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	T1 (mm)	cv (m³/h)	Weight (kg)
8650712000	20	Rp 3/4	136	73.7	30.5	24	234	120	44	140	64	16.3	3	1.31

Accessories

- final assembly set, figure 595 01
- final assembly set, long version, figure 595 02
- final assembly set, operating cover, figure 595 05
- extension set, figure 599 50 001
- blank cover plate, figure 865 00 001

Spare parts

- operating cap, figure 590 03 001

© Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe